




YTB5.0S Capacity: 5.0kVA




Proven durability & reliable power

Long seller YTB reborn with more advance features than ever.



- Stable & Hi power in class.
- Low fuel consumption.
- Low maintenance.
- Improved user friendly design.
- Robust frame & safety covers.



Control panel

SPECIFICATIONS

| | | Single Phase(2Wire) |
|--------------------------|---|--|
| Model | | YTB5.0S |
| Capacity ——— | kVA | 5.0 |
| | kW | 5.0 |
| Frequency | Hz | 50/60 |
| Revolutions | rpm-1 | 3000/3600 |
| No.of phase | | Single Phase(2 Wire) |
| Power factor | | 1.0 |
| Excitation system | | Brushless,self-excitation system |
| Drive system | | V-belt drive |
| Voltage(Standard) | V | 220, 110/220 |
| Ampere | Α | 22.7, 45.4 / 22.7 |
| Model | | TF90M |
| Туре | | Horizontal water-cooled,4-cycle diesel engine |
| Bore x stroke | mm | 85x87 |
| Displacement | liters | 0.493 |
| Cont.output | kW | 6.3 |
| Rated output | kW | 7.0 |
| Revolutions | min-1 | 2400 |
| Starting system | | Hand Starting or electric starting (optional) |
| Cooling system | | Radiator |
| Lubricating system | | Fully sealed forced lubrication with |
| | | trochoid pump & hydraulic regulator valve |
| • | | Direct injection |
| Lub. Oil capacity liters | lit/h | 2.2 |
| Fuel tank capacity | liters | 10.5 |
| | Capacity Frequency Revolutions No.of phase Power factor Excitation system Drive system Voltage(Standard) Ampere Model Type Bore x stroke Displacement Cont.output Rated output Revolutions Starting system Cooling system Lubricating system Lubricating system Lub. Oil capacity liters | kVA Capacity kW Frequency Hz Revolutions rpm-1 No.of phase Power factor Excitation system Feature factor Drive system V Voltage(Standard) V Ampere A Model Type Bore x stroke mm Displacement liters Cont.output kW Rated output kW Revolutions min-1 Starting system Cooling system Lubricating system Combustion system Lub. Oil capacity liters lit/h |

| | | | Single Phase(2Wire) |
|------|------------------|----|--|
| | Model | | YTB5.0S |
| Unit | Dimension length | mm | 1170 |
| | Dimension width | mm | 480 |
| | Dimension height | mm | 600 |
| | Net weight (dry) | kg | 189(Manual start) 200(Electric start) |

Standard Scope of Supply:

- 1. Tool kits
- 2. Additional V-Belt
- 3. Element F.O Strainer
- 4. Instruction Manual

Optional:

- 1. Electric Starting
- 2. Battery and cables
- 3. Wheel Castors

YANMAR CO.,LTD.

1-1, 2-choume, Yaesu, Chuo-ku, Tokyo, 104-8486, Japan Telephone: +81-3-3275-4914 Fax: +81-3-3278-1977 vanmar.com

Distributed by