



YANMAR

YM351A / YM357A

TRACTOR

51HP, 57HP

SMARTASSIST

GO NEXT

Take agriculture to the next level



YANMAR is a Japanese company with 100 years of history in building diesel engines. It has since grown to be a global leader in production of agricultural machinery, industrial diesel engines, engines for marine and pleasure boats, construction equipment and energy systems. With presence in over 66 countries, YANMAR enters the Philippines in joining the nations to redefine the agricultural industry and provide sustainable future for all the Filipinos.

FARM SMARTER

Using YANMAR's advanced technology, farming has never been easier. Check your fields from your smartphone.



WORK FASTER

Get more done with faster, more accurate operation.



POWERFUL & FUEL-EFFICIENT

YANMAR's original combustion technology gets the most out of every drop of fuel for a powerful engine that is long lasting.



QUALITY THAT'S BUILT TO LAST

Drivetrain and core parts are made with high-durability casting for long-lasting strength.



■ Main Specifications

| Model | | | YM351A | YM357A |
|----------------------|--------------------------------------|------------------------|---|-------------------------------|
| Engine | Maker | | YANMAR | |
| | Model | | 4TNV88 | 4TNV94L |
| | Type | | 4 Cylinders, Direct Injection, Vertical, Water-Cooled, Diesel | |
| | Total Displacement | L | 2.190 | 3.054 |
| | Gross Power | kW (HP) / rpm | 38.0 (51.0) / 2800 | 42.4 (57.0) / 2400 |
| | Fuel Tank | L | 50 | |
| Dimensions | Overall Length (without 3-point hit) | mm | 3330 | 3380 |
| | Overall Width | mm | 1580 | |
| | Overall Height | mm | 2570 | |
| | Wheel Base | mm | 1900 | 1970 |
| | Min. Ground Clearance | mm | 425 | |
| | Tread | mm | Front : 1252 (Standand) / 1404 | Rear : 1238 (Standand) / 1320 |
| Weight | kg | | 1680 | 1790 |
| Traveling System | Tire | inch | Front : 8 - 18 | Rear : 13.6 - 26 |
| | Clutch | | Dry, Single | |
| | Brake | | Mechanical, wet disk | |
| | Steering | | Hydrostatic power | |
| | Main shift | | synchronized (4stage) | |
| | Reverser | | synchronized Reverser | |
| | Number of shift | | 8 forward and 8 reverse | |
| | Travel speed | Forward / Reverse | km / hr | 2.4 - 28.0 / 2.4 - 28.0 |
| Hydraulic Unit | 3-Point Hitch | | Category 1 | |
| | Max. Lift Force | at lower link end | kN (kgf) | |
| Power Take off (PTO) | Type | | independent | |
| | Gear1 | PTO speed / engine rpm | 540 / 2430 | 540 / 2096 |
| | Gear2 | PTO speed / engine rpm | 740 / 2417 | 740 / 2064 |

Note: All technical data, measurement and weight are approximate, and the manufacturer has the right to make alteration without prior notice.

VISIT YOUR LOCAL YANMAR
WEBSITE: www.yanmar.com/ph



AUTHORIZED DEALER