






AW82V

Combine Harvester Top Sacker Model

82 HP







HIGH PERFORMANCE EVEN ON WET FIELD

With its high ground clearance (327mm), it protects the gear box from getting dirt as well as its long and wide crawler that exerts a relatively small amount of ground contact pressure.

SPECIFICATIONS

Model	YANMAR AW82V SX-PH			
Туре	Top Sacker			
Dimensions	Total length		mm	5030
	Total width		mm	2285
	Total height		mm	2905
Weight			kg	3180
Engine	Model		·	4TNV98T
	Туре			Water-cooled 4-cycle 4-cylinder vertical diesel
	Total displacement		СС	3318
	Output		kW HP/rpm	82 / 2400
	Starting mode		, ,	Electric Start
	Fuel tank capacity		L	90
Driving part	Crawlers	Width x Lenath (on around)	mm	500 x 1.700
	Mode of spec			HST side clutch hydraulic type
	Range shift gear			3
	Travel speed			Low Speed: 0 to 0.95
				Standard: 0 to 1.55
			m/sec	High Speed: 0 to 1.91
	Minimum ground clearance		mm	327
Reaping Section	Gap at the front end of crop divider		mm	2,060
	Cutter blades width		mm	1,975
	Cutting height range		mm	-50 to 1,000
	Reel	Diameter x width	mm	900 x 1,920
Threshing Section	Туре			Double rotor system
				Axial-flow bar type with vertical front rotor
	Front Rotor	Diameter x width	mm	400 x 520
	Threshing	Di		640 x 1,850
	Rotor	Diameter x width	mm	640 X 1,630
	Swing Separator (selection)		mm	850 x 1,410
	Concave size		m2	1.75
Grain Output	Method			2 grian output (top sacker 2 ports)
	Tank or hopper capacity		L	490
Electrical System			12 volt battery starting, lighting equipment, alarms electrical system	
Harvesting Capacity			ha/hr	0.2 / 0.7

Note: Specifications are subject to change without prior notice.

SPECIAL FEATURE: TECHNOLOGY 4.0



Your **YANMAR** machine in the palm of your hands!

Monitor, manage machine, measure area, set alarms using **SMARTASSIST** remote (SAR) feature.

Easily access SAR, personal copy of machine manuals, latest promotions through My Yanmar App. Scan the QR code to download for free!

MY YANMAR APP download links





Google Play

App Store







