

• THE TOUGHEST • PERFORMER • SECTION • SECTION





AGILE 4 CYLINDER ENGINE

12F+12R SYNCHROMESH TRANSMISSION

HEAVY LIFT CAPACITY

AERODYNAMICALLY DESIGNED

INTEGRATED SAFETY HVAC CABIN (OPTIONAL)






















FEATURES	S 90
Hydraulic lifting capacity	3000 kg
Auxiliary hydraulic circuit	2DA/2SA
SAFETY SWITCH	
Clutch Safety Switch	Yes
PTO Safety Switch	Yes
Neutral Safety Switch	Yes
CAPACITY (LTRS)(+/2%)	
Fuel tank (Ltr)	64
TURNING RADIUS	
Without Brakes	LHS-6.13, RHS-6.19
TYRE	
Front	12.4-24
Rear	18.4-30
DIMENSION & WEIGHT(+/-5%)	
Weight(kg)	3043 (Ballasted)
Wheel Base (mm)	2350
Total Length (mm)	4330
Total Width (mm)	1975
Height (mm) up to ROPS	2762
Min. Ground Clearance (mm)	405
Front Track (mm)	1628 (with Std. Width)
Rear Track (mm)	1508 (with Std. Width)
OTHERS	
Fuel Indicator gauge	Yes
Registration Plate with light	Yes
Front Tow Hook	Yes, inbuilt in front weight
Front & Rear Weights	Front- 30kgX2 and 25kgX4
	Rear- 2X34 kg (Each Side)
Drawbar	Swinging Drawbar
ROPS	Yes
OPTIONAL FEATURES	
Cabin	HVAC
Front Mudguard	Yes
Trailer Brake	НТВ/АТВ

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP