

YANMAR CO., LTD. YANMAR AMERICA CORP.

| ANMAR | | | | |
|-------------|------------------------------|--|----------|------------------------------------|
| Item | Part No. | Description | Quantity | Remarks |
| 1 | 129987-08020 | Leg, Flywheel Housing Mount | 2 | |
| 2 3 | 22137-100000 26107-100252 | Washer, M10 (Plain) Bolt, M10x1.5-25 (Flanged Hex Head) | 8 8 | |
| | | | | |
| | | | | |
| | | | - | MODELS 4TNV98 4TNV98T |
| | 2 ~ | | | |
| 9 9 9 | | | | |
| | 3 0 0 | | | |
| | | | | |
| | | | | DUNTING FEET I |



Installation Instructions

The flywheel housing leg kit has been designed so each leg can be mounted on the flywheel housing mounting pads only.

Hand tighten all bolts and nuts until assembly is completed, then torque according to specifications in Table 1. The numbers in () below reference the item numbers on page 1.

1. Install Mounting Legs (1) to flywheel housing mounting pads using Washer (2) and M10 x 1.5 - 25 bolt (3) provided in kit. Bolts used to mount shipped engines are the same size but not long enough and should not be used.

Table 1: Comply with torque standards in the table to avoid unexpected damage during installation or in the future.

| Diameter x Pitch | Kgf-m | Foot-Ibf | N-m |
|------------------|------------|-------------|-------------|
| M8 x 1.25 | 1.5 ~ 2.9 | 10.6 ~ 20.9 | 14.4 ~ 28.3 |
| M10 x 1.50 | 4.5 ~ 5.5 | 32.5 ~ 39.8 | 44.0 ~ 54.0 |
| M12 x 1.75 | 8.0 ~ 10.0 | 57.8 ~ 72.3 | 78.4 ~ 98.0 |

KFHF3 - MOUNTING FEET KIT INS-KFHF3-0011

PAGE 2 OF 2